



## Filter Wizard

DesignFilesSubsonic16Hz

Created on 06/18/2024



# Filter Wizard Design Report

Filter Requirements for High-Pass, 4th order Butterworth

Specifications: Optimize: Specific Parts; +Vs: 15; -Vs: -15

Gain: 0 dB


Passband: -0.1dB at 16Hz

Stopband: -60dB at 1.6Hz


Component Tolerances: Capacitor = 5%; Resistor = 1%; Inductor = 5%; Op Amp GBW = 20%

BOM: refer to BOM.csv file


Magnitude(dB)




Magnitude(Volts per Volt)




Phase(degrees)




Phase(radians)



Group Delay




Phase Delay







## Step Response




Input Impedance Magnitude



Input Impedance Phase



## Noise



## Stages

Your filter requires 2 op amp stage(s) with the following characteristics




**2nd order  
High-Pass  
Sallen Key**

	Target	Simulated
--	--------	-----------

Gain (V/V):	1	1 to 1
-------------	---	--------

$f_p$ (Hz):	10	10 to 11.5
-------------	----	------------

Q:	1.31	1.29 to 1.32
----	------	--------------




**2nd order  
High-Pass  
Sallen Key**

	Target	Simulated
--	--------	-----------


Gain (V/V):	1	1 to 1
-------------	---	--------

$f_p$ (Hz):	10	8.9 to 10
-------------	----	-----------


Q:	541m	537m to 549m
----	------	--------------



## Circuit



### BYPASS CAPACITORS



### SPARES Why The Spares?

