



Filter Wizard

Filter Wizard Design

Created on 06/24/2024



Filter Wizard Design Report

Filter Requirements for High-Pass, 4th order Butterworth

Specifications: Optimize: Specific Parts; +Vs: 15; -Vs: -15

Gain: 0 dB


Passband: -0.1dB at 200Hz

Stopband: -60dB at 20Hz


Component Tolerances: Capacitor = 5%; Resistor = 1%; Inductor = 5%; Op Amp GBW = 20%

BOM: refer to BOM.csv file


Magnitude(dB)




Magnitude(Volts per Volt)




Phase(degrees)




Phase(radians)




Group Delay




Phase Delay




Step Response




Input Impedance Magnitude



Input Impedance Phase



Noise



Stages

Your filter requires 2 op amp stage(s) with the following characteristics




**2nd order
High-Pass
Sallen Key**

	Target	Simulated
--	--------	-----------

Gain (V/V):	1	1 to 1
-------------	---	--------

f_p (Hz):	125	119 to 134
-------------	-----	------------

Q:	1.31	1.29 to 1.32
----	------	--------------




**2nd order
High-Pass
Sallen Key**

	Target	Simulated
--	--------	-----------


Gain (V/V):	1	1 to 1
-------------	---	--------

f_p (Hz):	125	111 to 125
-------------	-----	------------


Q:	541m	541m to 557m
----	------	--------------



Circuit



BYPASS CAPACITORS



SPARES Why The Spares?

