



## Filter Wizard

DesignFilesSubsonic12Hz

Created on 06/18/2024



# Filter Wizard Design Report

Filter Requirements for High-Pass, 4th order Butterworth

Specifications: Optimize: Specific Parts; +Vs: 15; -Vs: -15

Gain: 0 dB


Passband: -0.1dB at 12Hz

Stopband: -60dB at 1.2Hz


Component Tolerances: Capacitor = 5%; Resistor = 1%; Inductor = 5%; Op Amp GBW = 20%

BOM: refer to BOM.csv file


Magnitude(dB)




Magnitude(Volts per Volt)




Phase(degrees)




Phase(radians)



Group Delay




Phase Delay







Step Response




Input Impedance Magnitude



Input Impedance Phase



## Noise



## Stages

Your filter requires 2 op amp stage(s) with the following characteristics




**2nd order  
High-Pass  
Sallen Key**

	Target	Simulated
--	--------	-----------

Gain (V/V):	1	1 to 1
-------------	---	--------

$f_p$ (Hz):	7.5	6.87 to 7.75
-------------	-----	--------------

Q:	1.31	1.28 to 1.31
----	------	--------------




**2nd order  
High-Pass  
Sallen Key**

	Target	Simulated
--	--------	-----------


Gain (V/V):	1	1 to 1
-------------	---	--------

$f_p$ (Hz):	7.5	7.46 to 8.41
-------------	-----	--------------


Q:	541m	541m to 554m
----	------	--------------



## Circuit



### BYPASS CAPACITORS



### SPARES Why The Spares?

